


PROJECT NAME:

**CAMP TIMANOUS  
DINING HALL**

85 PLAINS RD.  
RAYMOND, ME 04071

SEAL:



THIS DRAWING IS THE PROPERTY OF  
SIMONS ARCHITECTS (SA) AND IS NOT  
TO BE COPIED OR REPRODUCED IN  
PART OR WHOLE.  
2024 © SIMONS ARCHITECTS, LLC

ISSUANCES

ISSUE FOR CONST. 03/01/2024


DATE OF ISSUE: 03/01/2024

PROJECT NUMBER: 2023-0050


STATUS: ISSUED FOR CONSTRUCTION

**VERTICAL  
CIRCULATION**


**A401**




1 EXTERIOR RAMP ELEVATION  
1/2" = 1'-0"




2 EXTERIOR RAMP ENLARGED FLOOR PLAN  
1/2" = 1'-0"




3 STONE STAIR SECTION, TYP  
1 1/2" = 1'-0"



4 TYP. GUARDRAIL SECTION  
1 1/2" = 1'-0"




5 RESTAURANT STAIR PLAN  
1/2" = 1'-0"



6 RESTAURANT EXPANSION STAIR PLAN  
1/2" = 1'-0"

**SYMBOL LEGEND**

ROOM NUMBER	ROOM NAME
101	101
DOOR NUMBER	101A
WINDOW NUMBER	101A
PARTITION TYPE	A3
PLUMBING FIXTURE	PF
EQUIPMENT/ ACCESSORY TAG	AC
FLOOR FINISH	WD
WALL/BASE FINISH	XY AB
FINISH TAG	WD
KEYNOTE	1








75 York Street  
Portland, Maine 04101  
simonsarchitects.com  
207.772.4656

PROJECT NAME:  
**CAMP TIMANOUS  
DINING HALL**

85 PLAINS RD.  
RAYMOND, ME 04071

SEAL:




THIS DRAWING IS THE PROPERTY OF SIMONS ARCHITECTS (SA) AND IS NOT TO BE COPIED OR REPRODUCED IN PART OR WHOLE.  
2024 © SIMONS ARCHITECTS, LLC

ISSUANCES  
ISSUE FOR CONST. 03/01/2024


DATE OF ISSUE: 03/01/2024  
PROJECT NUMBER: 2023-0050  
STATUS: ISSUED FOR CONSTRUCTION

**DETAILS**


**A501**




6 ROLL DOWN SHUTTER  
1 1/2" = 1'-0"




5 BASE CABINET W SINK - ADA  
1 1/2" = 1'-0"




3 BASE CABINET  
1 1/2" = 1'-0"



2 BASE CABINET @ BOTTLE FILLERS  
1 1/2" = 1'-0"



1 BASE - PULL OUT TRASH CABINET  
1 1/2" = 1'-0"




4 WOOD HOPPER/SHUTTER  
1 1/2" = 1'-0"



REFERENCE IMAGE OF EXISTING CONDITION

**SYMBOL LEGEND**

ROOM NUMBER	ROOM NAME
101	101
DOOR NUMBER	101A
WINDOW NUMBER	101A
PARTITION TYPE	A3
PLUMBING FIXTURE	PF
EQUIPMENT/ ACCESSORY TAG	AC
FLOOR FINISH	WD
WALL/BASE FINISH	XY AB
FINISH TAG	WD
KEYNOTE	1






EQUIPMENT & ACCESSORIES SCHEDULE		
TAG	EQUIPMENT DESCRIPTION	COMMENTS
AC6	TRASH / COMPOST / RECYCLING CAN	PROVIDED BY OWNER, CONTRACTOR INSTALLED
EQ1	WOOD SLAT ROLLING COUNTER SHUTTER, MANUALLY OPERATED	
EQ2	WOOD SLAT ROLLING COUNTER SHUTTER, MANUALLY OPERATED	
EQ3	ELECTRIC STACKING WASHER/DRYER	PROVIDED BY OWNER, CONTRACTOR INSTALLED
EQ4	CUBBIES	PROVIDED BY OWENR, GC TO SECURE TO WALL

FINISH LEGEND			
TAG	DESCRIPTION	DETAILS	
FLOORS	WD1	INTERIOR WOOD FLOORING	
	WD2	WOOD DECKING	
	CON	SEALED CONCRETE	SEALED CONCRETE
	RF	RESILIENT FLOORING COORD W/ KITCHEN DRAWINGS	ALTRO STRONGHOLD 30 SHEET, MIDNIGHT (K30421)
BASE	RB	RUBBER BASE - GREEN	JOHNSONITE, BASEWORKS 2 1/2" VL8 GRINCH
	TL1	COVE BASE	COORDINATE WITH WALL TILE TL1
	WD3	2" WOOD BASE CLR FINISH	
WALL	WD4	WOOD FRAMING/SHEATHING	
	PT1	PAINT - WHITE	
	PT2	PAINT - GREEN	
	FRP	FIBER REINFORCED PLASTIC WALL PANELING	
CEILING	GWB	GYPSUM WALL BOARD	ABUSE RESISTANT
	ACT	2X2 ACOUSTIC CEILING TILE	2X2 ACOUSTIC CEILING TILE
	WD5	EXPOSED WOOD CEILING	CUSTOM PLANKING, MATCH ROOF SHEATHING
OTHER	SS1	QUARTZ COUNTERTOP	1-1/2" THICK, COLOR AND MODEL TBD
	WD6	CABINETS	CLEAR COAT 3/4" PINE PLYWOOD

DOOR SCHEDULE									
NO.	LOCATION	TYPE	INT/EXT	DOOR FINISH	SIZE		FRAME FINISH	COMMENTS	
					HEIGHT	WIDTH			
101A	BARN DINING HALL	C	INT.	-	7' - 0"	4' - 0"	CLEAR COAT	FRAMED OPENING ONLY	
101B	BARN DINING HALL	C	INT.	-	7' - 0"	4' - 0"	CLEAR COAT	FRAMED OPENING ONLY	
101C	BARN DINING HALL	B	EXT.	PT-2	7' - 0"	3' - 0"	PT-2	REMOVABLE SCREEN PANELS	
102	DRY STORAGE	A	INT.	CLEAR COAT	7' - 0"	3' - 0"	PT-2		
103A	VESTIBULE	BB	EXT.	PT-2	7' - 0"	6' - 0"	PT-2	GLASS LITE (SEE ELEVATION BELOW)	
103B	KITCHEN	BB	INT.	CLEAR COAT	7' - 0"	6' - 0"	PT-2	ONE LEAF TO OPEN 180, REMOVABLE SCREEN PANELS	
104A	KITCHEN	B	INT.	PT-2	7' - 0"	3' - 0"	PT-2	REMOVABLE SCREEN PANELS	
104B	KITCHEN	B	INT.	PT-2	7' - 0"	3' - 0"	PT-2	REMOVABLE SCREEN PANELS	
106	HALL	C	INT.	-	7' - 0"	3' - 0"	PT-2	FRAMED OPENING ONLY	
107A	DISHWASHING	C	INT.	-	7' - 0"	4' - 0"	PT-2	FRAMED OPENING ONLY	
107B	DISHWASHING	C	INT.	-	7' - 0"	3' - 0"	PT-2	FRAMED OPENING ONLY	
108	DRY STORAGE	A	INT.	CLEAR COAT	7' - 0"	3' - 0"	PT-2		
109	PORCH	DD	EXT.	PT-2	7' - 0"	6' - 0"	PT-2	WOOD DOOR WITH REMOVABLE SCREEN PANELS	
110	RESTAURANT DINING HALL	DD	EXT.	PT-2	7' - 0"	6' - 0"	PT-2	WOOD DOOR WITH REMOVABLE SCREEN PANEL	


\* DESIGN INTENT IS TO MATCH EXISTING CONDITIONS IN BARN, VIF TRIM DIMENSIONS PRIOR TO FABRICATION



A WOOD SWING B SOLID CORE WOOD W/ LITE BB SOLID CORE WOOD W/ LITE (SCRN AND GLSS) C CASIED OPENING DD ENTRY DOORS SWING

WINDOW SCHEDULE						
NO.	LOCATION	TYPE	HEIGHT	WIDTH	SILL HEIGHT	COMMENTS
101	BARN DINING HALL	B	3' - 6"	6' - 0"	11' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.
103A	VESTIBULE	A	4' - 0"	2' - 0"	3' - 0"	
103B	VESTIBULE	A	4' - 0"	2' - 0"	3' - 0"	
106A	HALL	C	4' - 0"	3' - 0"	2' - 6"	
106B	OFFICE	C	4' - 0"	3' - 0"	2' - 6"	
109A	RESTAURANT DINING HALL EXPANSION	B	3' - 6"	6' - 0"	3' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.
109B	RESTAURANT DINING HALL EXPANSION	B	3' - 6"	6' - 0"	3' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.
109C	RESTAURANT DINING HALL EXPANSION	B	3' - 6"	6' - 0"	3' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.
109D	RESTAURANT DINING HALL EXPANSION	B	3' - 6"	6' - 0"	3' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.
109E	RESTAURANT DINING HALL EXPANSION	B	3' - 6"	6' - 0"	3' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.
109F	RESTAURANT DINING HALL EXPANSION	B	3' - 6"	6' - 0"	8' - 0"	SCREEN WINDOW TO MATCH EXISTING WITHIN BARN. PROVIDE INTERIOR SHUTTER TO MATCH EXISTING.

\* DESIGN INTENT IS TO MATCH EXISTING CONDITIONS IN BARN, VIF TRIM DIMENSIONS PRIOR TO FABRICATION



A FIXED GLASS B HOPPER SCREEN C OPERABLE GLASS



75 York Street  
Portland, Maine 04101  
simonsarchitects.com  
207.772.4656

PROJECT NAME:  
**CAMP TIMANOUS  
DINING HALL**

85 PLAINS RD.  
RAYMOND, ME 04071

SEAL:



THIS DRAWING IS THE PROPERTY OF SIMONS ARCHITECTS (SA) AND IS NOT TO BE COPIED OR REPRODUCED IN PART OR WHOLE.  
2024 © SIMONS ARCHITECTS, LLC

ISSUANCES

ISSUE FOR CONST. 03/01/2024

DATE OF ISSUE: 03/01/2024

PROJECT NUMBER: 2023-0050

STATUS: ISSUED FOR CONSTRUCTION

**SCHEDULES**

**A600**



**GENERAL NOTES:**

- REFERENCE ARCHITECTURAL PLANS FOR DIMENSIONS NOT SHOWN. REFERENCE MECHANICAL, ELECTRICAL, AND ARCHITECTURAL PLANS FOR SIZES AND LOCATIONS OF WALL AND SLAB OPENINGS, DUCTS, PIPING, CURBS, AND EQUIPMENT PADS. IN THE EVENT OF A CONFLICT BETWEEN THE DRAWINGS, SPECIFICATIONS, OR NOTES ON THE DRAWINGS, THE ENGINEER SHALL BE NOTIFIED PRIOR TO CONSTRUCTION.
- EXISTING DIMENSIONS AND CONDITIONS ARE FOR REFERENCE ONLY. CONTRACTOR SHALL VERIFY ALL EXISTING CONSTRUCTION AND DIMENSIONS IN THE FIELD PRIOR TO CONSTRUCTION OR FABRICATION. ALL DISCREPANCIES SHALL BE REPORTED TO THE ENGINEER PRIOR TO COMMENCING WORK.
- THE CONTRACTOR SHALL NOTIFY THE ENGINEER IF DEVIATIONS OR CHANGES ARE REQUIRED TO THE CONTRACT DOCUMENTS OR APPROVED SHOP DRAWINGS DUE TO INTERFERENCES, FABRICATION ERRORS, OR OTHER CAUSES.
- THE STRUCTURE IS SELF-SUPPORTING AND STABLE AFTER THE ENTIRE BUILDING IS COMPLETELY CONSTRUCTED. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR ERECTION PROCEDURES AND SEQUENCING DURING CONSTRUCTION AND ERECTION TO PROVIDE AND ENSURE LOCAL AND OVERALL STABILITY OF THE BUILDING AND ITS COMPONENTS DURING CONSTRUCTION AND ERECTION. THE CONTRACTOR SHALL RETAIN A LICENSED STRUCTURAL ENGINEER TO DESIGN TEMPORARY BRACING/SHORING AND DETERMINE WHERE THE TEMPORARY BRACING/SHORING IS NEEDED.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ERECTION PROCEDURES, SEQUENCING AND FOR COMPLYING WITH ALL APPLICABLE SAFETY REGULATIONS DURING THE WORK.
- SHOP DRAWINGS SHALL BE SUBMITTED ELECTRONICALLY AND WILL USUALLY BE RETURNED WITHIN 2 WEEKS OF RECEIPT.
- REFERENCE THE PROJECT SPECIFICATIONS FOR MATERIAL, WORKMANSHIP AND ADDITIONAL INFORMATION NOT COVERED IN THESE NOTES (WHERE APPLICABLE)

**DESIGN CRITERIA:**

- BUILDING CODES:**  
INTERNATIONAL BUILDING CODE (IBC), 2015 EDITION  
ASCE 7-10 MINIMUM DESIGN LOADS FOR BUILDING AND OTHER STRUCTURES
- SUPERIMPOSED DEAD LOADS:**  
RESIDENTIAL = 15 PSF
- LIVE LOADS:**  
RESIDENTIAL = 40 PSF
- SNOW LOADS:**  
GROUND SNOW LOAD (Pg) = 80 PSF  
SNOW EXPOSURE FACTOR (Ce) = 1.0  
SNOW LOAD IMPORTANCE FACTOR (Is) = 1.0  
THERMAL FACTOR (Ct) = 1.1  
FLAT ROOF SNOW LOAD (P) = 61.6 PSF + DRIFT

**FOUNDATION NOTES:**

- FOUNDATIONS HAVE BEEN DESIGNED USING A PRESUMED ALLOWABLE BEARING PRESSURE PER TABLE 1906.2 OF THE INTERNATIONAL BUILDING CODE BASED ON TYPICAL SOILS FOUND IN THIS AREA. IF CLAY, MUD, ORGANIC SILT, PEAT OR UNPREPARED FILL IS FOUND DURING CONSTRUCTION, NOTIFY ENGINEER IMMEDIATELY, AS THE ALLOWABLE LOADS USED IN DESIGN WILL NEED TO BE VERIFIED BY A GEOTECHNICAL ENGINEER. TRILLIUM ENGINEERING GROUP RECOMMENDS PROCURING A GEOTECHNICAL ENGINEER TO VERIFY EXISTING SOIL CONDITIONS.
- ALLOWABLE SOIL BEARING CAPACITY USED IN DESIGN = 2,000 PSF
- MINIMUM FROST DEPTH COVER = 4'-6" FOR EXTERIOR FOOTINGS BELOW FINAL EXTERIOR GRADE.
- EXCAVATION, BACKFILL, COMPACTION, GRADATION REQUIREMENTS, FOUNDATION DRAINAGE AND PERMANENT DEWATERING REQUIREMENTS SHALL BE PROVIDED BY A GEOTECHNICAL ENGINEER.
- CONCRETE SLABS ON GRADE SHALL BE CONSTRUCTED ON A MINIMUM 12" THICK LAYER OF PROPERLY COMPACTED STRUCTURAL FILL, UNLESS OTHERWISE DIRECTED BY A GEOTECHNICAL ENGINEER.
- FOUNDATIONS SHALL BEAR ON UNDISTURBED NATIVE SOIL, UNLESS NOTED OTHERWISE. THE CONTRACTOR SHALL NOTIFY THE GEOTECHNICAL AND STRUCTURAL ENGINEER IF ANY UNSUITABLE SOILS ARE ENCOUNTERED PRIOR TO PLACING FOUNDATIONS.
- FOUNDATION WALLS AND SLAB-ON-GRADES SHALL REACH THEIR FULL 28 DAY COMPRESSIVE STRENGTH PRIOR TO BACKFILLING. THE CONTRACTOR SHALL PROVIDE TEMPORARY SHORING/BRACING FOR WALLS WHEN BACKFILL IS PLACED PRIOR TO CONCRETE ACHIEVING ITS FULL 28 DAY STRENGTH. CONTRACTOR SHALL PROVIDE TEMPORARY SHORING/BRACING FOR WALLS AND OTHER STRUCTURAL ELEMENTS PRIOR TO INSTALLATION OF PERMANENT BRACING/FLOOR/STRUCTURE.
- PROTECT FOUNDATIONS FROM FROST AND KEEP BOTTOM OF TRENCH DRY DURING CONSTRUCTION. IF GROUNDWATER IS ENCOUNTERED NEAR OR ABOVE THE BASE OF THE FOOTINGS, EXCAVATIONS SHALL BE DEWATERED DURING CONSTRUCTION. SURFACE WATER SHALL BE DIVERTED AWAY FROM EXCAVATIONS.
- DO NOT UNDERMINE EXISTING FOUNDATIONS OF ADJACENT STRUCTURES. CONTRACTOR SHALL BE RESPONSIBLE FOR THE SHORING, BRACING AND UNDERPINNING OF EXISTING STRUCTURES DURING EXCAVATION, BACKFILLING, AND CONSTRUCTION. CONTRACTOR SHALL SLOPE EXCAVATIONS TO ACHIEVE SOIL STABILITY.

**CONCRETE NOTES:**

- ALL WORK SHALL CONFORM TO IBC 2015 REFERENCED EDITIONS OF "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE" (ACI 318) AND "SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS" (ACI 301).
- REQUIRED CONCRETE PARAMETERS ARE AS FOLLOWS:

LOCATION	MAX W/C RATIO	fc	AIR-ENTRAINMENT	MAX DENSITY
FOUNDATIONS, FOOTINGS, & FOUNDATION WALLS	--	3,500 PSI	5% ± 1 1/2%	150 PCF
INT. SLAB-ON-GRADE	0.50	3,000 PSI	2% ± 1 1/2%	150 PCF
EXT. SLAB-ON-GRADE	0.50	4,500 PSI	5% ± 1 1/2%	150 PCF
SLAB-ON-METAL-DECK	--	3,000 PSI	2% ± 1 1/2%	115 PCF

WHERE, W/C = WATER TO CEMENT RATIO AND  
fc = COMPRESSIVE STRENGTH OF CONCRETE AT 28 DAYS

USE PORTLAND CEMENT TYPE II, IN CONFORMANCE WITH ASTM 150  
AIR ENTRAINING ADMIXTURES SHALL CONFORM TO ASTM C 260  
ADMIXTURES SHALL CONFORM TO ASTM C 494  
FLY ASH USED AS ADMIXTURES SHALL CONFORM TO ASTM C 618

- MAXIMUM AGGREGATE SIZE SHALL BE 3/4", IN CONFORMANCE WITH ASTM C33.
- CALCIUM CHLORIDE OR ADMIXTURES CONTAINING CALCIUM CHLORIDE IS NOT PERMITTED.
- MAXIMUM SLUMP AFTER THE ADDITION OF A WATER-REDUCING ADMIXTURE IS 6 INCHES.
- CONTRACTOR SHALL NOT PLACE CONCRETE ON FROZEN GROUND OR IN WATER. ADEQUATE EQUIPMENT SHALL BE PROVIDED FOR HEATING CONCRETE MATERIALS AND PROTECTING CONCRETE DURING NEAR-FREEZING OR FREEZING WEATHER. REFERENCE ACI 306, AS NOTED ABOVE, FOR RECOMMENDATIONS FOR COLD WEATHER CONCRETING.
- VERTICAL CONSTRUCTION JOINTS IN WALLS SHALL NOT EXCEED A SPACING OF 40 FEET, U.N.O.
- ANCHOR BOLTS SHALL BE HEADED RODS AND CONFORM TO ASTM F1554, GRADE 36 KSI WELDABLE STEEL, U.N.O. ON DRAWINGS. PROVIDE GALVANIZED ANCHOR BOLTS WHERE IN CONTACT WITH PRESSURE TREATED LUMBER.
- REINFORCING BARS SHALL CONFORM TO ASTM A615, GRADE 60, DEFORMED BARS.
- WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185 AND BE PROVIDED IN FLAT SHEETS. PROVIDE ADEQUATE SUPPORT FOR WWF TO ENSURE PROPER LOCATION WITHIN SLAB DURING CONCRETE PLACEMENT.
- MINIMUM CONCRETE COVER FOR REINFORCEMENT SHALL BE AS FOLLOWS:  
A. CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3 INCHES  
B. FORMED CONCRETE IN CONTACT WITH EARTH OR EXPOSED TO WEATHER 2 INCHES  
C. CONCRETE NOT EXPOSED TO EARTH OR WEATHER IN SLABS & WALLS 1 1/2 INCHES
- WELDING OF REINFORCEMENT IS NOT PERMITTED.
- PROVIDE NON-SHRINK GROUT BENEATH LEVELING PLATES & BEARING PLATES w/ MINIMUM COMPRESSIVE STRENGTH OF 7,000 PSI AT 28 DAYS.
- PROVIDE CONTINUOUS REINFORCEMENT AT ALL CORNERS AND INTERSECTIONS. SEE TYPICAL FOUNDATION WALL DETAILS ON FOUNDATION DETAILS SHEET.
- REINFORCING BARS AND ALL EMBEDDED ITEMS, INCLUDING ANCHOR BOLTS, MUST BE ACCURATELY PLACED AND ADEQUATELY SECURED BEFORE CONCRETE IS PLACED. "WET SETTING" OF STEEL COLUMN ANCHOR BOLTS INTO CONCRETE IS STRICTLY PROHIBITED.
- UNLESS NOTED ON DRAWINGS, FOLLOW ACI STANDARDS FOR LAP SPLICE LENGTHS OF REINFORCING BARS.

BAR SIZE	#3	#4	#5	#6	#7	#8	#9
3000 & 3500 PSI CONCRETE	18"	24"	30"	36"	48"	56"	64"
4500 PSI CONCRETE	16"	20"	24"	30"	40"	48"	54"


**WOOD NOTES:**

- ALL TIMBER FRAMING SHALL BE IN ACCORDANCE WITH IBC 2015 REFERENCED EDITIONS OF THE AITC TIMBER CONSTRUCTION MANUAL AND AF&PA NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION (NDS).
- ALL FRAMING SHALL BE SPRUCE-PINE-FIR, No.2 OR BETTER U.N.O. AND HAVE A MAXIMUM MOISTURE CONTENT OF 19%.
- ALL WOOD IN CONTACT WITH MASONRY OR CONCRETE OR EXPOSED TO WEATHER SHALL BE PRESSURE TREATED (PT) SOUTHERN YELLOW PINE.
- WHERE "LVL" IS NOTED ON DRAWINGS, PROVIDE LAMINATED VENEER LUMBER, WHICH HAS THE FOLLOWING MINIMUM ALLOWABLE STRESSES:  
• Fb = 2800 PSI Fc = 3000 PSI (PARALLEL TO GRAIN)  
• Fv = 285 PSI Fc = 750 PSI (PERPENDICULAR TO GRAIN)  
• Ft = 2150 PSI E = 2,000,000 PSI
- WHERE "PSL" IS NOTED ON DRAWINGS, PROVIDE PARALLAM STRAND LUMBER, WHICH HAS THE FOLLOWING MINIMUM ALLOWABLE STRESSES:  
• Fb = 2400 PSI Fc = 2500 PSI (PARALLEL TO GRAIN)  
• Fv = 190 PSI Fc = 545 PSI (PERPENDICULAR TO GRAIN)  
• Ft = 1995 PSI E = 1,800,000 PSI
- ALL ENGINEERED LUMBER THAT IS EXPOSED TO WEATHER SHALL BE WOLMANIZED.
- ALL FLOOR SHEATHING SHALL BE 3/4" TONGUE AND GROOVE, GLUED AND NAILED TO FLOOR FRAMING WITH 8d RINK SHANK NAILS AT 6" o.c. AT SUPPORTED PANEL EDGES, 12" o.c. AT INTERMEDIATE SUPPORTS UNLESS NOTED OTHERWISE ON DRAWINGS.
- ALL ROOF SHEATHING (8" WOOD PANEL, SEE ARCH) AND WALL SHEATHING (1 1/2") SHALL BE APA PERFORMANCE-RATED, ATTACH TO SUPPORTED PANEL EDGES WITH 8d NAILS AT 6" o.c. AND AT INTERMEDIATE SUPPORTS WITH 8d NAILS AT 12" o.c. U.N.O. SEE DRAWINGS FOR MORE STRINGENT NAILING REQUIREMENTS AT WOOD SHEAR WALLS.
- SHEATHING SHALL BE ORIENTED WITH LONG DIMENSION PERPENDICULAR TO THE SUPPORTS AND BE CONTINUOUS OVER TWO OR MORE SUPPORTS. STAGGER ALL JOINTS & PROVIDE ADEQUATE JOINT SPACING (1/8" TYP) AS RECOMMENDED BY MANUFACTURER.
- PROVIDE FULL DEPTH BLOCKING AT ENDS AND INTERIOR SUPPORTS OF ALL JOISTS AND RAFTERS WHERE JOISTS AND RAFTERS FRAME OVER SUPPORTS. PROVIDE 1x3 DIAGONAL BRIDGING OR FULL DEPTH SOLID BLOCKING FOR EACH 8'-0" OF SPAN FOR ALL JOISTS AND RAFTERS.
- WHERE BEAMS ARE LABELED ON PLAN, DO NOT SPLICE BEAM NOR ANY PLY OF BEAM BETWEEN SUPPORTS.
- ALL CONNECTION HARDWARE SHALL BE BY SIMPSON STONG-TIE (OR APPROVED EQUIVALENT) AND SHALL BE HOP-DIPPED GALVANIZED. HARDWARE IN CONTACT WITH PRESSURE TREATED (PT) LUMBER SHALL BE GALVANIZED G185 (ZMAX). REFER TO MANUFACTURERS LITERATURE FOR PROPER INSTALLATION GUIDELINES.
- FASTENERS USED IN CONTACT WITH PRESSURE TREATED (PT) LUMBER SHALL BE HOT-DIPPED GALVANIZED, STAINLESS STEEL, OR OTHER FINISH APPROVED BY ENGINEER.
- ALIGN COLUMNS SUCH THAT COLUMNS BEAR CONTINUOUSLY TO FOUNDATION SUPPORT. INSTALL ADDITIONAL SOLID BLOCKING WITHIN FLOOR PACKAGE TO PROVIDE CONTINUITY OF LOAD PATH.
- PROVIDE HORIZONTAL BLOCKING FOR ALL LOAD BEARING WALLS AT 4'-0" O.C. VERTICAL, MAXIMUM.
- SUBMIT SHOP DRAWINGS FOR ALL PREFABRICATED WOOD JOISTS AND WALL PANELS TO ENGINEER FOR REVIEW PRIOR TO CONSTRUCTION.

**PREFABRICATED WOOD TRUSS NOTES:**

- FABRICATE, SUPPLY AND ERECT WOOD TRUSS AS SHOWN ON THE DRAWINGS AND AS SPECIFIED. WORK TO INCLUDE ANCHORAGE, BLOCKING, CURBING, MISCELLANEOUS FRAMING AND BRACING.
- SEE ARCHITECTURAL DRAWINGS FOR ALL TRUSS PROFILES AND DIMENSIONS.
- ROOF TRUSSES SHALL BE DESIGNED FOR:  
TOP CHORD DEAD LOAD - 13 PSF  
TOP CHORD SNOW LOAD - 61.6 PSF\* (BALANCED)  
BOTTOM CHORD DEAD LOAD - 8 PSF  
BOTTOM CHORD LIVE LOAD - 10 PSF (30 PSF IN ATTIC AREAS IF REQUIRED)  
\* CONSIDER UNBALANCED SNOW LOAD PER ASCE 7-10
- GABLE END TRUSSES SHALL HAVE VERTICALS AT 16" o.c. CALCULATE WIND LOADS PER CRITERIA INDICATED IN THE DRAWINGS AND NOTES
- ALLOWABLE LIVE LOAD DEFLECTION FOR PREFABRICATED TRUSSES = L/480
- TRUSS MANUFACTURER SHALL SUBMIT DRAWINGS INDICATING THE FOLLOWING:  
A. SPAN, SLOPE AND SPACING OF TRUSSES  
B. REQUIRED BEARING WIDTH  
C. DESIGN LOADS, AS APPLICABLE:  
i. TOP CHORD LIVE LOAD  
ii. TOP CHORD DEAD LOAD  
iii. BOTTOM CHORD LIVE LOAD  
iv. BOTTOM CHORD DEAD LOAD  
v. CONCENTRATED LOADS AND THEIR POINTS OF APPLICATION  
vi. WIND AND SEISMIC CRITERIA  
D. REACTIVE FORCES  
E. LUMBER SIZE, SPECIES AND GRADE FOR EACH MEMBER  
F. LOCATION OF ANY REQUIRED CONTINUOUS LATERAL BRACING (CLB)  
G. CALCULATED DEFLECTION RATIO AND/OR MAXIMUM DEFLECTION FOR LIVE AND TOTAL LOAD  
H. CONNECTION REQUIREMENTS FOR:  
i. TRUSS TO TRUSS GIRDERS  
ii. TRUSS PLY TO PLY  
iii. FIELD SPLICES
- TRUSSES SHALL BE FABRICATED IN A PROPERLY EQUIPPED MANUFACTURING FACILITY OF A PERMANENT NATURE. TRUSSES SHALL BE MANUFACTURED BY EXPERIENCED WORKMEN, USING PRECISION CUTTING, JIGGING AND PRESSING EQUIPMENT MEETING REQUIREMENTS OF ANS/ITP 1-1995, SECTION 4. TRUSS MEMBERS SHALL BE ACCURATELY CUT TO LENGTH ANGLE AND TRUE TO LINE TO ASSURE PROPER FITTING JOINTS WITHIN TOLERANCES SET FORTH IN ANS/ITP 1-1995, SECTION 4, AND PROPER FIT WITH OTHER WORK.
- FOLLOW TRUSS MANUFACTURERS RECOMMENDATIONS & LATEST EDITION OF THE BCSP FOR HANDLING, INSTALLATION AND BRACING OF TRUSSES. ERECTION OF TRUSSES IS SOLELY THE RESPONSIBILITY OF THE CONTRACTOR. CONSULT TRUSS MANUFACTURER OR INDEPENDENT ENGINEER IF FURTHER DESIGN ASSISTANCE IS NEEDED.
- MANUFACTURER SHALL FURNISH DESIGN DRAWINGS BEARING SEAL AND REGISTRATION NUMBER OF A CIVIL OR STRUCTURAL ENGINEER LICENSED IN STATE WHERE TRUSSES ARE TO BE INSTALLED. DRAWINGS SHALL BE APPROVED BY ARCHITECT OR STRUCTURAL ENGINEER OF RECORD PRIOR TO FABRICATION.

**LEGEND:**




**ABBREVIATION:**

AB	ANCHOR BOLT	L	ANGLE
ABV	ABOVE	LL	DOUBLE ANGLE
ADDL	ADDITIONAL	LB	POUND
ARCH	ARCHITECT	LF	LINEAR FOOT
&	AND	LLH	LONG LEG HORIZONTAL
		LLV	LONG LEG VERTICAL
B/FTG, BOF	BOTTOM OF FOOTING	MAX	MAXIMUM
BLDG	BUILDING	MECH	MECHANICAL
BLW	BELOW	MFR	MANUFACTURER
BM	BEAM	MIN	MINIMUM
BOT	BOTTOM	MISC	MISCELLANEOUS
BRG	BEARING		
BTWN	BETWEEN	NF	NEAR FACE
		NO	NUMBER
C	STRUCTURAL STEEL CHANNEL	NS	NEAR SIDE
CANT	CANTILEVER	NTS	NOT TO SCALE
CFMF	COLD-FORM METAL FRAMING		
CP	CAST-IN-PLACE CONCRETE		
CJ	CONTROL JOINT	OC	ON CENTER
CL	CENTERLINE	OF	OUTSIDE FACE
CLR	CLEAR	OPNG	OPENING
CMU	CONCRETE MASONRY UNIT	OPP	OPPOSITE
CONJ	CONSTRUCTION JOINT		
COL	COLUMN	P	PIER DESIGNATION
CONC	CONCRETE	PL	PLATE
CONN	CONNECTION	PP	PARTIAL PENETRATION WELD
CONT	CONTINUOUS	PREFAB	PREFABRICATED
CONTR	CONTRACTOR	PSF	POUNDS PER SQUARE FOOT
CP	COMPLETE PENETRATION WELD	PSI	POUNDS PER SQUARE INCH
CY	CUBIC YARD	REINF	REINFORCING STEEL
		REQ, REQD	REQUIRED
DIA	DIAMETER	RD	ROOF DRAIN
DIM	DIMENSION		
DISCONT	DISCONTINUOUS		
DWG	DRAWING	SC	SLIP CRITICAL
		SECT	SECTION
(E), EX, EXIST	EXISTING	SHEATH	SHEATHING
EA	EACH	SIM	SIMILAR
EF	EACH FACE	SOG	SLAB-ON-GRADE
EL ELEV	ELEVATION	SPAC	SPACING
EQ	EQUAL	SPECS	SPECIFICATIONS
EQUIP	EQUIPMENT	SS	STAINLESS STEEL
ES	EACH SIDE	STD	STANDARD
EW	EACH WAY	STIFF	STIFFENER
EXP	EXPANSION	STL	STEEL
EXT	EXTERIOR	STR	STRAIGHT
		STRUCT	STRUCTURAL
F	FOOTING DESIGNATION	T	TOP
FDN	FOUNDATION	T&B	TOP AND BOTTOM
FF	FINISH FLOOR	TOC, T/CONC	TOP OF CONCRETE
FLG	FLANGE	T/FTG, TOP	TOP OF FOOTING
FLR	FLOOR	TEMP	TEMPERATURE
FT	FOOT	T/SHLF	TOP OF SHELF
FTG	FOOTING	TISLAB	TOP OF SLAB
FV	FIELD VERIFY	TIS/TL	TOP OF STEEL
		T/WALL	TOP OF WALL
G	GAGE	TS	STRUCTURAL TUBING
GALV	GALVANIZED	TYP	TYPICAL
		UNO	UNLESS NOTED OTHERWISE
HOR, HORIZ	HORIZONTAL		
HSS	HOLLOW STRUCTURAL SHAPE	VER, VERT	VERTICAL
HT	HEIGHT	VIF	VERIFY IN FIELD
IF	INSIDE FACE	W	STRUCTURAL STEEL WIDE FLANGE
IN	INCH	w/	WITH
INFO	INFORMATION	w/O	WITHOUT
		WP	WORK POINT
JT	JOINT	WT	WEIGHT
		WWF	WELDED WIRE FABRIC
K	KIP (1 KIP = 1,000 LBS)		
KSI	KIPS PER SQUARE INCH		



CLIENT:



**CAMP TIMANOUS  
DINNING HALL  
RAYMOND, MAINE**

ISSUED	DESCRIPTION	DATE	BY	100% CONSTRUCTION DOCUMENTS		NUMBER
				ZVP		
A		03-01-2024	ZVP			

SHEET TITLE:

**STRUCTURAL NOTES**

DESIGNED BY:	ZVP
DRAWN BY:	ZVP
PROJECT NUMBER:	22-224

**S0.0**



**CAMP TIMANOUS  
DINNING HALL**  
RAYMOND, MAINE


ISSUED	DESCRIPTION	BY	DATE
1	100% CONSTRUCTION DOCUMENTS	ZVP	03-01-2024

SHEET TITLE:

**FOUNDATION PLAN**

DESIGNED BY: ZVP  
DRAWN BY: ZVP  
PROJECT NUMBER: 22-224

**S1.0**



- FOUNDATION PLAN NOTES**
1. TOP OF SLAB-ON-GRADE ELEVATION = XX' - XX" AND EQUALS REFERENCE TOP OF SLAB ELEVATION XX' - XX"
  2. TOP OF CONCRETE ELEVATIONS ARE NOTED (+/- X'-X") FROM REFERENCE ELEVATION.
  3. TYPICAL T/FOOTING ELEVATIONS ARE AS FOLLOWS, UNO:  
T/FTG = (4' - 0")
  5. SEE S2.0 FOR TYPICAL FOUNDATION DETAILS.

**CAMP TIMANOUS  
DINNING HALL**  
RAYMOND, MAINE


ISSUED NUMBER	DESCRIPTION	BY	DATE
A	100% CONSTRUCTION DOCUMENTS	ZVP	03-01-2024

SHEET TITLE:

**FIRST FLOOR  
FRAMING PLAN**


DESIGNED BY: ZVP  
DRAWN BY: ZVP  
PROJECT NUMBER: 22-224

**S1.1**



- NOTES:  
1. PROVIDE SIMPSON JOIST HANGERS AT ALL JOIST ENDS, TYP.  
2. SEE ARCH FOR T/DECK ELEVATION  
3. SEE S2.0 & S3.0 FOR ADDITIONAL DETAILS

**CAMP TIMANOUS  
DINNING HALL**  
RAYMOND, MAINE



NOTE: CONTRACTOR TO PROVIDE A \$5,000 ALLOWANCE FOR MISC REPAIRS TO EXISTING TIMBER FRAME BARN STRUCTURE. REPAIRS TO BE FIELD DETERMINED DURING CONSTRUCTION.








- NOTES:
1. PROVIDE SIMPSON JOIST HANGERS AT ALL JOIST ENDS, TYP.
  2. WINDOW HEADERS SHALL BE (3)-2X10'S, U.N.O.
  3. WHERE HEADER SIZES ARE NOTED ON PLANS, PROVIDE (2) PLY HEADER TO FORM BOX HEADER PER 1/S3.0
  4. PROVIDE (3)2X6 STUDS AT ALL CORNERS, COLUMNS, AND HOLD DOWN LOCATIONS, U.N.O.
  5. ALL EXTERIOR WALLS SHALL BE SHEATHED ON ONE SIDE WITH 7/16" APA RATED SHEATHING. NAIL EXTERIOR SHEATHING PANEL EDGES @ 6" O.C. BLOCK AND STAGGER ALL PANEL EDGES. SPACE NAILS AT 12" O.C. AT INTERMEDIATE PANEL SUPPORTS, TYP U.N.O.
  6.  $\overleftarrow{D1}$  INDICATES SPAN OF 8" WOOD PLANK (MATCH EXISTING). SEE ARCH FOR SPECIFICATIONS.

ISSUED NUMBER	DESCRIPTION	DATE
		BY
A	100% CONSTRUCTION DOCUMENTS	ZVP

SHEET TITLE: **ROOF FRAMING PLAN**





DESIGNED BY:	ZVP
DRAWN BY:	ZVP
PROJECT NUMBER:	22-224





1 TYPICAL SLAB-ON-GRADE DETAILS  
NTS

2 TYPICAL FOUNDATION WALL DETAILS - SINGLE LAYER OF REINF  
NTS









3 TYPICAL FOUNDATION WALL SECTION AT BUILDING TRANSITION  
3/4" = 1'-0"

4 TYPICAL FOUNDATION WALL SECTION AT EXISTING WALL  
3/4" = 1'-0"

5 TYPICAL FOUNDATION WALL SECTION  
3/4" = 1'-0"

6 TYPICAL SONOTUBE DETAIL  
NTS



7 TYPICAL THROUGH WALL PENETRATION DETAIL  
NTS

8 TYPICAL SOG CONTROL JOINT LAYOUT  
NTS

11 TYPICAL SLAB DETAIL AT DOOR  
NTS


12 TYPICAL THICKENED SLAB UNDER WOOD COL  
NTS

**CAMP TIMANOUS  
DINNING HALL**  
RAYMOND, MAINE


ISSUED	DESCRIPTION	DATE
A	100% CONSTRUCTION DOCUMENTS	03-01-2024

SHEET TITLE:  
**TYPICAL FOUNDATION DETAILS**  
DESIGNED BY: ZVP  
DRAWN BY: ZVP  
PROJECT NUMBER: 22-224






1 TYPICAL FRAMING DETAILS - DIMENSIONAL LUMBER  
3/4" = 1'-0"




- NOTES:
- EXTERIOR BEARING WALL HEADERS TO BE (2) 2x10 VERT, TYP UNO.
  - EXTERIOR NON-LOAD BEARING WALL HEADERS TO BE (2) 2x8 VERT, TYP UNO.
  - WHERE OTHER HEADER SIZES ARE NOTED ON PLAN, FORM BOX HEADER W/ (2) 2x6 HORIZ UNO.
  - PROVIDE # OF FULL HEIGHT KING STUDS ON EACH SIDE OF OPENING TO MATCH 1/2 OF INTERRUPTED STUDS @ WALL OPENING, UNO. MINIMUM OF (2) FULL HEIGHT KING STUDS @ EACH SIDE OF OPENING.
  - NON LOAD-BEARING HEADERS SUPPORTED BY MINIMUM OF (1) JACK STUD. LOAD BEARING HEADERS SUPPORTED BY COLUMNS PER PLAN/NOTES.
  - WINDOW SILL PLATES EXCEEDING 6FT SHALL BE (2) 2x (FLAT), MATCH STUD WIDTH.


2 TYPICAL HEADER DETAIL  
1" = 1'-0"



3 TRUSS SECTION  
3/4" = 1'-0"




4 PREFABRICATED TRUSS SECTIONS & DETAILS  
1" = 1'-0"




5 SECTION - TRUSS BEARING ON HEADER  
1" = 1'-0"

6 SECTION - TRUSS BEARING ON WALL  
1" = 1'-0"



7 ROOF TRUSS END DETAIL  
1" = 1'-0"




8 TYPICAL ROOF TRUSS END DETAIL  
1" = 1'-0"

**CAMP TIMANOUS  
DINNING HALL**  
RAYMOND, MAINE

ISSUED	DESCRIPTION	DATE
A	100% CONSTRUCTION DOCUMENTS	03-01-2024

SHEET TITLE:  
**TYPICAL FRAMING DETAILS**  
DESIGNED BY: ZVP  
DRAWN BY: ZVP  
PROJECT NUMBER: 22-224





1 Foodservice Equipment Plan  
1/4" = 1'-0"

### Foodservice Equipment Schedule

Item #	Qty.	Description
1	1	Walk-In Cooler
2	1	Evaporator Coil, Cooler
3	1	Compressor, Cooler
4	1	Walk-In Freezer
5	1	Evaporator Coil, Freezer
5.1	1	Drain Line Heat Tape
6	1	Compressor, Freezer
7	6	Sheet Pan Rack
8	12	Shelving Unit
10	17	Shelving Unit
11	1	Exhaust Hood (Left)
12	1	Exhaust Hood (Right)
13	1	Range, 6-Burner
14	1	Equipment Stand
15	1	Griddle
16	2	Convection Oven, Double
17	1	Mixer Stand w/ Utensil Rack
18	1	Mixer, 20-Quart
19	1	Worktable with Sinks
20	1	Pass-Thru Shelf
21	3	Hand Sink
22	1	Worktable
23	2	Heated/Holding Cabinet
24	1	Steamer
25	1	Serving Counter
26	1	Ice Bin
27	1	Ice Machine
28	1	Utility Cart
29	1	Sink, 3-Compartment
30	1	Shelving Unit
31	1	Dishtable, Clean
32	1	Dishwasher, Door-Type, Tall, Ventless
33	1	Dishtable, Soiled
34	1	Mop Sink Cabinet
35	1	Serving Counter, Salad Bar
36	1	Mobile Slicer Table
37	1	Slicer (Existing)
38	2	Pitcher Filler
39	1	Sink, Drop-In

### Foodservice Equipment Mechanical Schedule

ITEM #	QTY	DESCRIPTION	Electrical			Plumbing				Gas		Ventilation				Notes		
			Volts	Phase	Watts	HP	FL Amps	Hot Water	Cold Water	Direct Waste	Indirect Waste	Size	BTU's	Exhaust CFM's	Diameter		Supply CFM's	Depth
1	1	Walk-In Cooler	120 V	1														
2	1	Evaporator Coil, Cooler	115 V	1	120 W													
3	1	Compressor, Cooler	208 V	1		0.8												
4	1	Walk-In Freezer	120 V	1														
5	1	Evaporator Coil, Freezer	208 V	1	2010 W													
5.1	1	Drain Line Heat Tape	120 V	1	500 W													
6	1	Compressor, Freezer	208 V	1		3.5												
7	6	Sheet Pan Rack																
8	12	Shelving Unit																
10	17	Shelving Unit																
11	1	Exhaust Hood (Left)	120 V	1										2375 CFM	1' - 4"			
12	1	Exhaust Hood (Right)											1465 CFM	1' - 0"				
13	1	Range, 6-Burner									3/4"	215000.0 Btu/h						
14	1	Equipment Stand																
15	1	Griddle	120 V	1														
16	2	Convection Oven, Double	120 V	1		1/2					3/4"	135000.0 Btu/h						
17	1	Mixer Stand w/ Utensil Rack									3/4"	100000.0 Btu/h						
18	1	Mixer, 20-Quart	115 V	1		1/2												
19	1	Worktable with Sinks					1/2"	1/2"		2"								
20	1	Pass-Thru Shelf																
21	3	Hand Sink					1/2"	1/2"		1 1/2"								
22	1	Worktable																
23	2	Heated/Holding Cabinet	120 V	1	2000 W													
24	1	Steamer	208 V	1	6000 W						3/4"							
25	1	Serving Counter																
26	1	Ice Bin									3/4"							
27	1	Ice Machine	208 V	1							1/2"							
28	1	Utility Cart									3/4"							
29	1	Sink, 3-Compartment					1/2"	1/2"		2"								
30	1	Shelving Unit																
31	1	Dishtable, Clean																
32	1	Dishwasher, Door-Type, Tall, Ventless	208 V	1		2		1/2"		1 1/2"			250 CFM					
33	1	Dishtable, Soiled					1/2"	1/2"		2"								
34	1	Mop Sink Cabinet					1/2"	1/2"		2"								
35	1	Serving Counter, Salad Bar	115 V	1		1/4					3/4"							
36	1	Mobile Slicer Table																
37	1	Slicer (Existing)	115 V	1		1/2					4.0 A							
38	2	Pitcher Filler									3/8"							
39	1	Sink, Drop-In					1/2"	1/2"		1 1/2"								



**Camp Timanous**  
85 Plains Road - Raymond, Maine

Project Name

Project #: 2023-0050

Drawn By: TJM

Date: 03/01/2024

Status: ISSUE FOR CONSTRUCTION

Drawing Name


FOODSERVICE EQUIPMENT PLAN & SCHEDULE

Sheet Number

**FS-1**

Scale: 1/4" = 1'-0"





① Foodservice Equipment Plan, Electric  
1/4" = 1'-0"

### ELECTRICAL CONNECTION LEGEND

- DUPLEX RECEPT., 20-AMP, 120-VOLT, GROUND TYPE, HORIZONTAL MOUNT
- SIMPLEX RECEPT., 20-AMP, 120-VOLT, GROUND TYPE, HORIZONTAL MOUNT
- SPECIAL PURPOSE OUTLET, 120-VOLT, GROUND TYPE, HORIZONTAL MOUNT
- SPECIAL PURPOSE OUTLET, 120/208-VOLT, AS INDICATED, GROUND TYPE, HORIZONTAL MOUNT
- JUNCTION BOX WITH CONDUIT, STUB AS INDICATED FOR DIRECT CONNECTION
- DROP CORD WITH TWIST LOCK
- STUB-UP/ DFA MAIN FEED AS INDICATED, TERMINATES AS JUNCTION BOX (SEE ABOVE).
- J-BOX DATA
- FIELD WIRING
- SAFETY DISCONNECT SWITCH (SDS)
- TELEPHONE JACK
- SWITCH
- MANUAL PULL (FIRE SUPPRESSION SYSTEM)
- AFF ABOVE FINISHED FLOOR
- DFA DOWN FROM ABOVE
- BTC BRANCH TO CONNECTION
- C.O. CONVENIENCE OUTLET
- E.C. ELECTRICAL CONTRACTOR
- NIC NOT IN CONTRACT

○ Electrical Legend  
1/4" = 1'-0"

### Electrical Rough-In Schedule

Item #	Qty.	Description	Volts	Phase	HP	Watts	FL Amps	Connection Type	Plug Type	RI Height	Remarks
1	1	Walk-In Cooler	120 V	1			15.0 A	Direct Connection		9' - 0"	Door Panel, Lights and Alarm
2	1	Evaporator Coil, Cooler	115 V	1		120 W	2.3 A	Direct Connection		9' - 0"	
3	1	Compressor, Cooler	208 V	1	0.8		9.6 A	Direct Connection		3' - 0"	Verify Location
4	1	Walk-In Freezer	120 V	1			15.0 A	Direct Connection		9' - 0"	Door Panel, Lights and Alarm
5	1	Evaporator Coil, Freezer	208 V	1		2010 W	11.7 A	Direct Connection		9' - 0"	
5.1	1	Drain Line Heat Tape	120 V	1		500 W	4.3 A	Cord and Plug	NEMA 5-15P	6' - 0"	By Electrical Contractor
6	1	Compressor, Freezer	208 V	1	3.5		25.3 A	Direct Connection		3' - 0"	Verify Location
11	1	Exhaust Hood (Left)	120 V	1			15.0 A	Direct Connection		9' - 0"	Lights and Controls
15	1	Griddle	120 V	1			1.0 A	Cord & Plug	NEMA 5-15P	2' - 0"	
16	2	Convection Oven, Double	120 V	1	1/2		7.7 A	Cord and Plug	NEMA 5-15P	4' - 2"	Two connections per unit required.
18	1	Mixer, 20-Quart	115 V	1	1/2		6.0 A	Cord and Plug	NEMA 5-15P	4' - 2"	
23	2	Heated/Hodling Cabinet	120 V	1		2000 W	16.0 A	Cord and Plug	NEMA 5-20P	2' - 0"	
24	1	Steamer	208 V	1		6000 W	29.0 A	Cord and Plug	NEMA L6-30P	4' - 2"	
27	1	Ice Machine	208 V	1			11.0 A	Direct Connection		6' - 0"	
32	1	Dishwasher, Door-Type, Tall, Ventless	208 V	1	2		75.9 A	Direct Connection		2' - 0"	
35	1	Serving Counter, Salad Bar	115 V	1	1/4		3.7 A	Cord and Plug	NEMA 5-15P	0' - 0"	Flush Floor Outlet
37	1	Slicer (Existing)	115 V	1	1/2		4.0 A	Cord and Plug	NEMA 5-15P	4' - 2"	Existing equipment, Verify all utilities.

**TJM** CONSULTING INC.  
Foodservice Consulting and Design  
2 Main Street, Suite 17-301C  
Biddeford, Maine 04005  
(207) 215-4736  
tom@tjmconsulting.net

**Camp Timanous**  
85 Plains Road - Raymond, Maine

Project Name

Project #: 2023-0050

Drawn By: TJM

Date: 03/01/2024

Status: ISSUE FOR CONSTRUCTION

Drawing Name



**FOODSERVICE  
EQUIPMENT  
ELECTRICAL  
PLAN**

Sheet Number

**FS-2**

Scale: 1/4" = 1'-0"






1 Foodservice Equipment Plan, Plumbing  
1/4" = 1'-0"

### Plumbing Rough-In Schedule

Item #	Qty.	Description	Hot Water		Cold Water		Indirect Waste		Direct Waste		Gas		Remarks
			Size	RI Height	Size	RI Height	Size	Connection Type	Size	RI Height	Size	BTU's	
2	1	Evaporator Coil, Cooler					3/4"	Funnel Floor Drain					
5	1	Evaporator Coil, Freezer					3/4"	Funnel Floor Drain					
13	1	Range, 6-Burner								3/4"	215000.0 Btu/h	3' - 0"	
15	1	Griddle								3/4"	135000.0 Btu/h	3' - 0"	
16	2	Convection Oven, Double								3/4"	100000.0 Btu/h	3' - 0"	
19	1	Worktable with Sinks	1/2"	1' - 2"	1/2"	1' - 2"	2"	Floor Sink, Half-Grate					
21	3	Hand Sink	1/2"	1' - 8"	1/2"	1' - 8"			1 1/2"	1' - 8"			
24	1	Steamer			3/4"	1' - 2"	3/4"	Floor Sink, Half-Grate					
26	1	Ice Bin					3/4"	Floor Sink, Half-Grate					
27	1	Ice Machine			1/2"	5' - 0"	3/4"	Floor Sink, Half-Grate					
29	1	Sink, 3-Compartment	1/2"	1' - 2"	1/2"	1' - 2"			2"	0' - 8"			
32	1	Dishwasher, Door-Type, Tall, Ventless			1/2"	1' - 2"	1 1/2"	Floor Sink, Half-Grate					
33	1	Dish Table, Soiled	1/2"	1' - 2"	1/2"	1' - 2"			2"	1' - 0"			
34	1	Mop Sink Cabinet	1/2"	3' - 0"	1/2"	3' - 0"			2"	0' - 3"			
35	1	Serving Counter, Salad Bar					3/4"						
38	2	Pitcher Filler			3/8"	1' - 2"	3/4"	Floor Sink, Half-Grate					
39	1	Sink, Drop-In	1/2"	1' - 8"	1/2"	1' - 8"			1 1/2"	1' - 8"			



Quick Disconnect Gas Hose Connection Detail

Project Name

Project #: 2023-0050

Drawn By: *TJM*

Date: 03/01/2024

Status: *ISSUE FOR CONSTRUCTION*

Drawing Name

**FOODSERVICE EQUIPMENT PLUMBING PLAN**

Sheet Number

**FS-3**

Scale: 1/4" = 1'-0"